

■ EMPTY ENCLOSURES FOR DISTRIBUTION ASSEMBLIES WITH FRONT AND SIDE SOCKETS



■ REFERENCE STANDARDS

EN 60670-1

EN 60670-24

■ MARKINGS AND DIRECTIVES



■ VERSIONS



6 DIN



11 DIN



Side cut-outs on right and left sides for DOMO Series (50x60mm flange)

■ TECHNICAL CHARACTERISTICS

Protection degree:	IP55
Installation temperature:	-25°C +60°C
Self extinguishing degree [GWT]:	650°C
Material:	Thermoplastic (Halogen Free)
Impact resistance (IK degree):	IK08
Cable entries:	PG16-PG21-PG29
Insulation class:	Class II (double insulation)
Dissipable power according to CEI 23-49 Standard:	Size 6 DIN 9W Size 11 DIN 15W
Colour:	Grey RAL7035

■ BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Limited resistance	Resistant	Resistant	Not resistant	Not resistant	Resistant	Not resistant	Limited resistance

Resistance values to chemical agents have to be considered indicative. For further information and specific substances, contact the technical service.